

# MONTREAL COMFORT


## TECHNICAL SPECIFICATIONS



- Dimensions:** 56-58 cm seat centres  
61 cm depth  
100 + 15 cm height
- Backrest:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell. Optional headrest with seat shell. Polyurethane density 55 Kg/m<sup>3</sup>.
- Seat:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell. The seat pan folds by means of an automatic noiseless maintenance-free double spring. Polyurethane density 65 Kg/m<sup>3</sup>.
- Side panel:** Texturized injected polypropylene, 80mm  
End row panels completely upholstered.  
Concealed floor fixation system.
- Armrest:** Straight-shaped texturized injected polypropylene.
- Volume:** 0.19 m<sup>3</sup>/unit
- Weight:** 19.00 Kg not assembled

# MONTREAL COMFORT

## DRAWING



## OPTIONS



Fixation to the floor



Slope



Movable seat



Ref 975 (More upright backrest)



On steps



Embroidered logo



Row labels



Seating numbering



Fixed seat



Tip-up armrest



Riser-fixed

## CERTIFICATES

	Fabrics	Fire Barrier	Foam
BS 5852:2006	•		
BS-EN 1021-1:2006	•		
CAL TB 117-2013, SECTION 1	•		
UNE 23.727-90 1R (M1)	•	•	
UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006	•	•	•
BS 5852:1979 Parte 1		•	