ROMA PLUS PL

TECHNICAL SPECIFICATIONS

|	
Dimensions:	57 a 59 cm seat centres 53 cm depth 100 cm height
Backrest:	Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell. Polyurethane density 55 Kg/m³.
Seat:	Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell. The seat pan folds by means of an automatic noiseless maintenance-free double spring. Polyurethane density 65 Kg/m³.
Side panel:	Texturized injected polypropylene, 70mm. Anti - panic polystyrene writing pad system with interior steel structure, located in the interior of the side panel. End row panels completely upholstered. Concealed floor fixation system.
Armrest:	Rectangular texturized injected polypropylene.
Volume:	0.15 m³ / unit
Weight:	18 Kg not assembled

Euro Seating reserves the right to modify the dimensions and characteristics without prior notice. All dimensions and specifications are given for information purposes only.

DRAWING

620mm [24 3/8"]

1000mm [39 3/8"]

640mm [25 1/8"]

530mm [20 7/8"]

1000mm [39 3/8"]

800mm [31 5/8"]

450mm [17 3/4"]

1000mm [39 3/8"]

570mm [22 1/2"]

800mm [31 1/2"]

OPTIONS

Fixation to the floor

Slope

Movable seat

Ref 975 (More upright backrest)

Embroidered logo

Row labels

Seating numbering

Desk

CERTIFICATES

	Fabrics	Fire barrier	Mousse	Seat
BS 5852:2006	•			
BS-EN 1021-1:2006	•			
CAL TB 117-2013, SECTION 1	•			
UNE 23.727-90 1R (M1)	•	•		
UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006	•	•	•	•
BS 5852:1979 Parte 1		•		

AIDIMA INSTITUTO TECNOLÓGICO MUEBLE, MADERA, EMBALAJE Y AFINES

ffmo

FIRA Member of

ISO 9001 BUREAU VERITAS Certification

ISO 14001 BUREAU VERITAS Certification

AENOR Ecodiseño UNE-EN ISO 14006