

TECHNICAL SPECIFICATIONS



Dimensions: 54 - 56 cm seat centres
57 cm depth
100 cm height

Backrest: Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell.
Polyurethane density 55 Kg/m³

Seat: Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell.
The seat pan folds by means of an automatic noiseless maintenance-free double spring.
Polyurethane density 65 Kg/m³


Side panel: Texturized injected polypropylene, 40mm
End row panels completely upholstered
Concealed floor fixation system

Armrest: Rounded texturized injected polypropylene


Volume: 0.16 m³ / unit

Weight: 18.20 Kg not assembled

DIMENSIONS AND DRAWING



OPTIONS



CERTIFICATES

BS 5852:2006
BS-EN 1021-1:2006
CAL TB 117-2013, SECTION 1
UNE 23.727-90 1R (M1)
UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006
BS 5852:1979 Parte 1

Fabric	Fire Barrier	Foam
•		
•		
•		
•	•	
•	•	•
	•	



Estadio Municipal de Ipurúa. Zona VIP.
Eibar. Gipuzkoa. SPAIN



Ghelamco Arena - KAA GENT. Gante.
BELGIUM



GKS Tychy Stadium. Tychy. POLAND

EURO SEATING AROUND THE WORLD

